

# Product Data

Type	Home-Cinema-System with active subwoofer system
Engineering Principle	Front: 2-way closed system Center: 2-way closed system Surround: 2-way closed system Subwoofer: Bandpass system
Nom. /Music power handling	Front: 100 watts Center: 100 watts Surround: 100 watts
Musical output	Subwoofer: 100 watts
SPL (1 watt/1m)	85 dB
Frequency response	Front: 120...25.000 Hz Center: 120...25.000 Hz Surround: 120...25.000 Hz Subwoofer: 38...140 Hz (adjustable)
Crossover frequency	Front: 5.000 Hz Center: 5.000 Hz Surround: 5.000 Hz Subwoofer: 80...140 Hz (adjustable)
Woofers	Front: 1 x 80 mm (3.2"), Aluminum finish Center: 2 x 80 mm (3.2"), Aluminum finish Surround: 1 x 80 mm (3.2"), Aluminum finish Subwoofer: 1 x 200 mm (8"), Aluminum finish
Tweeter	Front: 1 x 15 mm (1"), aluminum Center: 1 x 15 mm (1"), aluminum Surround: 1 x 15 mm (1"), aluminum
Special Features	Front: Coax system Wall brackets included  Center: Wall brackets included  Surround:

	<p>Wall brackets included</p> <p>Subwoofer: Adjustable crossover frequency Adjustable bass level SC-technology</p> <p>5 years warranty for front-,center- and rear- speakers 2 years warranty for subwoofer</p>
Nominal Impedance	4...8 ohms
Dimensions (WxHxD)	<p>Front: 8.9 x 9 x 10.6 cm (3.5 x 3.5 x 4.2)</p> <p>Center: 19.6 x 8.9 x 10.6 cm (7.7 x 3.5 x 4.2)</p> <p>Surround: 8.9 x 9 x 10.6 cm (3.5 x 3.5 x 4.2)</p> <p>Subwoofer: 23 x 38 x 42 cm (9.1 x 14.2 x 15.8)</p>
Weight	<p>Front: 0.6 kg</p> <p>Center: 1.3 kg</p> <p>Surround: 0.6 kg</p> <p>Subwoofer: 9.4 kg</p>
Power consumption	0,42 Watt
Available accessories	Loudspeaker stand LS 90.2
Carton Content	<p>Canton Movie 75</p> <p>Wallmounts</p> <p>Equipment feet</p> <p>Manual</p>