

# CS-64BS

## WIDE RANGE SPEAKER

The CS-64BS is the voice alarm certification product. The CS-64BS Wide range speaker features an ABS resin enclosure and stainless steel bracket for all weather durability. It is comprised of a high-efficiency weather-resistant horn and a high quality sound cone speaker, providing clear and highly directional sound reproduction.



Order no: CS-64BS  
 Alternative products: VX-3008F, VX-3004F,  
 VX-3016F, SX-2000SM, SX-2000AO,  
 SX-2100AO, VX-2000, VM-3360VA,  
 VM-3240VA, VM-3240E, VM-3360E, VP-3504,  
 VP-3154, VP-3304, VP-2421, VP-2421incl,  
 VP-2241, VP-2241incl, VP-2122incl, VP-2122,  
 VP-2064, VP-2064incl

### Specifications

Frequency response	130 Hz - 13 kHz
Connection	Ceramic screw terminals, thermal fuse, external connection box, 5-wire BS-compliant
Sensitivity (1#V, 1#n) (combined)	96 dB (1 W, 1 m at 330 Hz to 3.3 kHz pink noise) 93 dB (1 W, 1 m at 100 Hz to 10 kHz pink noise) 81 dB (1 W, 4 m at 100 Hz to 10 kHz pink noise)
Rated input	6 W
Tappings	6 / 3 / 1 W (100 V), 6 / 3 / 1.5 / 0.5 W (70 V)
Dimensions (W x H x D)	233 x 224 x 249 mm
Dimensions (ø x D)	x 249 mm
Finish	ABS resin, paint, papyrus white (RAL 9018 or equivalent)
Operating temperature	-20 °C to +55 °C

# CS-64BS

WIDE RANGE SPEAKER

Appearance

