



PRISMA PAR 50

SPECIFICATIONS / TECHNICAL DATA REV A

KEY FEATURES

IP65 Rated Exterior High-Power UV Wash Par Luminaire
50 Degree Wide Beam Angle
365nm Peak True UV Wavelength
Zero Visible Light Output

SPECIFICATIONS

Dynamic Effects

- . 50° Beam Angle
- . Variable Dimming Curve Modes
- . High Speed Electronic Strobe
- . Beam Uniformity
- . LCD Display
- . 2W High Power UV Led
- . 20,000 Hour Average Led Life

Control

- . DMX Modes: 3
- . DMX Channels: 1, 2, 4
- . RDM (Remote DMX) Protocol Support
- . Art-Net Protocol Support
- . Master/Slave Modes
- . Onboard 4 Button Touch Control Panel

Connections

- . Data Connectors: 5-pin XLR In/Out
- . Locking Power Connector

Construction / Physical / Performance

- . Dimensions (LxWxH): 7.55 x 5.90 x 12.36 in. / 192 x 150 x 314mm
- . Weight: 7.05 lbs. / 3.2kg
- . DB Rating: 41DN @ 1M

Electrical

- . Input Voltage: AC 100-240V, 50/60Hz
- . Amperage: 110v/0.34A, 240V/0.24A
- . Power Consumption: 83W
- . Fuse: T2A/250V





PRISMA PAR 50

SPECIFICATIONS / TECHNICAL DATA REV A

Certifications / Qualifications / Thermal

- . IP Rating: IP65 Rating
- . Approvals: ROHS, CE Approved
- . Cooling: Air Cooled
- . Maximum Temperature (Ambient): 113° F (45° C)
- . Minimum Temperature (Ambient): 14° F (-10° C)

What's Included

- . 14 AWG Locking Power Cable

Optional Accessories

- . Prisma Par Black Glass (PSG852)



192mm
(7.55 in.)



314 mm
(12.36 in.)

150 mm
(5.90 in.)

MAGMATIC