
VX-3000 Series / Remote Microphone / Key Extension / **RM-300X / RM-210F**



Features

- For both emergency and general purpose broadcast
 - Zone selection or all call
 - PC-programmable system software permits desired functions to be assigned to individual function keys (equipped with 2 LED indicators)
 - RM-210F: Key extension unit with 10 additional keys
 - Up to 7 RM-210F Remote Microphone Extension units can be used with each RM-300X Remote Microphone
-

Specifications

	RM-300X	RM-210F
Power Source	24VDC (operating range: 15 - 40VDC), supplied from the audio input unit or DC input power supply connector (when the optional AD-246 power supply unit used)	From remote microphone
Current Consumption	Under 240mA	20mA max. (from remote microphone)
Audio Output	0dBV, 600Ohm, balanced	-
External Microphone Input	-40dB, 2.2kΩ, unbalanced, mini jack, phantom powering	-
Frequency Response	100Hz – 20kHz	-
Distortion	Under 1%	-
Signal-to-noise Ratio	Over 60dB	-
Volume Control	Microphone volume control, Monitor speaker volume control	-
Connectable Extensions	7	-
Maximum Cable Distance	1,200m	-
Finish	ABS resin, black	ABS resin, black
Dimensions (W x H x D)	190 x 76.5 x 215 mm (gooseneck microphone excluded)	110 x 76.5 x 215 mm
Weight	850g	350g